

ROLL-A-COVER INT'L
 36 SARGENT DR.
 BETHANY, CT 06524

Tel: 203-393-7292
 Fax: 203-286-2012
 WWW.ROLLACOVER.COM

SCALE: NTS
 SALESMAN: M. MORRIS
 DRAWN BY: B. TAYLOR

JOB NAME & ADDRESS:
 5 BAY HIGH WIND SILL
 HD1" RAFTER


ORIGINATION REVISIONS
 REVISIONS
 REVISIONS
 REVISIONS
 REVISIONS

DATE: 7-9-19

DRAWING #:
 MW-JCN-01C

SHEET #:
 W/SILL

1
 01 OPERABLE LT SILL



2'-3"

- RAC RAFTER
- RAC SILL
- (2) #10 X 1" SELF-TAPPING P.H. SCREW WITH 1/2" WASHER
- RAC HIGH WIND SILL
- (6) #10 X 2" AT 16" O.C.
(2) MIN. AT 16" O.C. WHEN ONLY 1 TRACK PRESENT
- .090 ALUMINUM PAN FLASHING - BY RAC WHERE APPLICABLE
- WATER & ICE MEMBRANE - BY OTHERS
- COUNTERFLASHING & WATER PROTECTION - BY OTHERS
- 1 3/4" SILL LVL FLASHED TO BUILDING/SUPPORT -
 - MUST BE INSTALLED STRAIGHT, LEVEL, PLUM WITH NO DEVIATIONS AND PARALLEL TO REAR HEADER LVL.
 - ALL FASTENERS TO BE COUNTERSUNK BELOW SURFACE
 - WRAPPED WITH WEATHERPROOFING MEMBRANE (WATER & ICE) ON TOP BUT NOT GLUED DOWN.
 - PITCHED 1/4" PER 1' TO THE OUTSIDE NO MORE NO LESS.
 - TO BE INSTALLED BY OTHERS
- LVL MUST BE SECURELY FASTENED TO SUPPORT AND ABLE TO WITHSTAND RAC LOADS. RECOMMEND 100% CONTINUOUS STRUCTURAL SUPPORT UNDER ENTIRETY OF LVL. BY OTHERS. MINIMUM 8" CURB RECOMMENDED.
- ANY REQUIRED DRAINAGE FOR WATER CONTROL - BY OTHERS