



- RAC RAFTERS
- (2) #10 X 2-1/2" SELF TAPPING P.H. SCREWS
- RAC SILL
- (2) #10 X 1" SELF-TAPPING P.H. SCREW WITH 1/2" WASHER
- RAC HIGH WIND SILL
- #10 X 2"
- AT 16" O.C.
- (2) MIN. AT 16" O.C. WHEN ONLY 1 TRACK PRESENT
- .090 ALUMINUM PAN FLASHING
- BY RAC WHERE APPLICABLE
- WATER & ICE MEMBRANE
- BY OTHERS
- 1 3/4" SILL LVL FLASHED TO BUILDING/SUPPORT-
- MUST BE INSTALLED STRAIGHT, LEVEL, PLUM WITH NO DEVIATIONS AND PARALLEL TO REAR HEADER LVL.
 - ALL FASTENERS TO BE COUNTERSUNK BELOW SURFACE
 - WRAPPED WITH WEATHERPROOFING MEMBRANE (WATER & ICE) ON TOP BUT NOT GLUED DOWN.
 - PITCHED 1/4" PER 1' TO THE OUTSIDE NO MORE/NO LESS.
 - TO BE SUPPLIED & INSTALLED BY OTHERS
- *** PLEASE SEE RAC RECOMMENDED LVL ATTACHMENT DETAIL FOR ADDITIONAL INFORMATION
- LVL MUST BE SECURELY FASTENED TO SUPPORT AND ABLE TO WITHSTAND RAC LOADS. RECOMMEND 100% STRUCTURAL SUPPORT UNDER ENTIRETY OF LVL. BY OTHERS. MINIMUM 8" CURB RECOMMENDED.

1
01 OPERABLE SILL DESIGN

DRAWING #: MM-LVL-01A	JOB NAME & ADDRESS: HD10mm RAFTER HIGH WIND TRACK DESIGN VARYING BAY WIDTH		SCALE: NTS	ROLL-A-COVER INT'L 36 SARGENT DR. BETHANY, CT 06524 Tel: 203-393-7292 Fax: 203-286-2012 www.rollacover.com	
	SHEET #: 1 OF 1	ORIGINATION DATE: 8-22-25	REVISED REVISED REVISED	SALESMAN: DRAWN BY: B. TAYLOR	